

Figure 1

09295577-042299




Figure 2

062240-04299




Figure 3a




Figure 3b

Start Figure 4




Figure 4(a)

09295577-042299




Figure 4(b)

Customer Information - Netscape

File Edit View Go Communicator Help

Back Forward Reload Home Search Netscape Print Security

Bookmarks Location http://csp-msi.net/concerts/reserve2.html What's Related

Concert Reservation System

CUSTOMER INFORMATION	
Name as appear on CC	Richard Halavais
Phone	714-693-1171
Email	hal@msintergate.com
CC Number	4111111111111111
Expiration (MM/YY)	Month 09 / Year 99 ... example: 12/99
<div>Reserve Seats</div> <div>Clear Choices</div>	

28

29

Document: Done

Start Microsoft Word - ticket... Paint Shop Pro - imag Customer Informatio...

10:52 AM

Figure 4(c)

662240" / 556260




Figure 4(d)

662240" 456260




Figure 4(e)

End Figure 4

Start Figure 5

Begin Program

```
<Markup language>

<REM --- Imports the file "datasource.inc" which creates variable "datasource" which is used
to tell markup language datasource to connect to.          --- >

<INCLUDE NAME="database\datasource.inc">

<REM --- In case a database or other type of error occurs, this display the error message. -
-- >

<ERROR>

<FONT FACE="Verdana, Arial" SIZE="+1"><B>An Error Has Occurred</B></FONT><P>

<FONT FACE="Verdana, Arial" SIZE="-1"><B>Error Message = :i_errortext

</B></FONT><P>

<FONT FACE="Verdana, Arial" SIZE="-1"><B>database Error =

:i_databaseerrortext</B></FONT><P>

<FONT FACE="Verdana, Arial" SIZE="-1"><B>database Error = :i_databaseerrorstmt

</B></FONT><P>

</ERROR>

<REM --- Begin normal markup language here          --- >

<markup language>

<HEAD>

<TITLE>Ticketing & Reservation System</TITLE>

</HEAD>

<BODY BACKGROUND="images/background.jpg" TEXT="#000000" LINK="#006666"

VLINK="#006666">

<CENTER>

<IMG SRC="images/masthead_concerts.gif" HEIGHT=60 WIDTH=280><P>

<FONT FACE='Verdana,Arial' SIZE=-1><B>To begin reserving your seat(s), please select

the concert date/time you wish to attend next to the performer you want to

see:</B></FONT>
```

09295577.042299
662240.7556260

```
<TABLE BORDER=0 CELSPACING=5 CELLPADDING=5>
```

```
<REM --- Begin database query to retrieve all performances that is --- >
```

```
<REM --- currently available. Will loop until all available --- >
```

```
<REM --- performing artists and their performances are listed. --- >
```

```
<REM --- Part of the return from the query are the links that will --- >
```

```
<REM --- take you to the next step of the reservation. --- >
```

```
<database DBNAME=":datasource"
```

```
    database="SELECT id, name, picture, sequence
```

```
    FROM category
```

```
    WHERE active=1 AND parent=-1
```

```
    ORDER BY sequence"
```

```
    ALIAS="concert">
```

```
<databaseFETCH ALIAS="concert">
```

```
<WHILE NOTALIAS=i_databaseempty>
```

```
<TR>
```

```
<TD COLSPAN=2>
```

```
<FONT FACE="Verdana,Arial" SIZE=+1><B>:concert_name</B></FONT>
```

```
</TD></TR><TR><TD VALIGN="top">
```

```
<img src=images/:concert_picture align=top border="1">
```

```
</TD><TD>
```

```
<Markup language DBNAME=":datasource"
```

```
    database="SELECT id, name, date, time
```

```
    FROM category
```

```
    WHERE active=1 AND parent=:concert_id
```

```
    ORDER BY date, time"
```

```
    OUTPUT="<FONT FACE='Verdana,Arial' SIZE=-1><B>
```

```
<A HREF='reserve1.ihtml?&id=:1':2</A>
```

```
</B></FONT><p>">
```

```
</TD></TR><TR><TD COLSPAN=2><HR></TD></TR>
```

```
<databaseFETCH ALIAS="concert">
```

09265577 042699

```

</WHILE ALIAS=i_databaseempty>

</database ALIAS="concert">

</TABLE>

</BODY>

</markup language>

```

processing then passes to:

```

<Markup language>

<REM --- Imports the file "datasource.inc" which creates the    --- >

<REM --- variable "datasource" which is used to tell Markup language which    --- >

<REM --- database datasource to connect to.                    --- >

<INCLUDE NAME="database\datasource.inc">

<REM In case a database or other type of error occurs, this will display the error message. >

<ERROR>

<FONT FACE="Verdana,Arial" SIZE="+1"><B>An Error Has Occurred</B></FONT><P>

<FONT FACE="Verdana,Arial" SIZE="-1"><B>Error Message =

:i_errortext</B></FONT><P>

<FONT FACE="Verdana,Arial" SIZE="-1"><B>database Error =

:i_databaseerrortext</B></FONT><P>

<FONT FACE="Verdana,Arial" SIZE="-1"><B>database Error =

:i_databaseerrorstmt</B></FONT><P>

</ERROR>

<REM --- Begin normal markup language here --- >

<markup language>

<HEAD>

<TITLE>Ticketing & Reservation System - Select Seat(s)</TITLE>

</HEAD>

<REM --- All seats clicked will pass its information to a input box, "newseats". When done,
the information will be passed to "process.ihtml" and be processed by "reserve2.ihtml". --- >

<REM --- This code allows the ability to select multiple seats before proceeding to the next
step of reservation process. Other features include listing the selected seats in the

```

"number" text box to show the seats that has been clicked. This script also alters the button text to be grammatically correct. --- >

```
<SCRIPT LANGUAGE="JavaScript">
```

```
<!--
```

```
function selectseat(idnum, seatnum)
```

```
{
```

```
    reserved = document.seats.number.value;
```

```
    if (reserved == "")
```

```
    {
```

```
        document.seats.newseats.value = "<Markup language DBNAME=:"+datasource
```

```
        database='INSERT INTO basket (custid, pid, qty) VALUES (:'+custid, "+idnum+",
```

```
        1)'><database DBNAME=:"+datasource database='SELECT cost FROM products WHERE
```

```
        id="+idnum+"><databaseFETCH><iEQ NAME='ticketprice'
```

```
        VALUE=:"+1></database><iEQ NAME='total' VALUE=<iEVAL EXPR=:"+ticketprice +
```

```
        :+"total' PREC='2'>><Markup language DBNAME=:"+datasource database='INSERT INTO
```

```
        orderdetail (pid, oid, qty, sell) VALUES ("+idnum+", :+"oid, 1, :+"ticketprice)'>;
```

```
        document.seats.number.value = seatnum;
```

```
        document.seats.button1.value = "Reserve Seat";
```

```
        document.seats.button2.value = "Clear Choice";
```

```
    }
```

```
    else
```

```
    {
```

```
        document.seats.newseats.value += "<Markup language DBNAME=:"+datasource
```

```
        database='INSERT INTO basket (custid, pid, qty) VALUES (:'+custid, "+idnum+",
```

```
        1)'><database DBNAME=:"+datasource database='SELECT cost FROM products WHERE
```

```
        id="+idnum+"><databaseFETCH><iEQ NAME='ticketprice'
```

```
        VALUE=:"+1></database><iEQ NAME='total' VALUE=<iEVAL EXPR=:"+ticketprice +
```

```
        :+"total' PREC='2'>><Markup language DBNAME=:"+datasource database='INSERT INTO
```

```
        orderdetail (pid, oid, qty, sell) VALUES ("+idnum+", :+"oid, 1, :+"ticketprice)'>;
```

```
        document.seats.number.value = reserved+" "+seatnum;
```

```
document.seats.button1.value = "Reserve Seats";
```

```
document.seats.button2.value = "Clear Choices";
```

```
}
```

```
}
```

```
function clear()
```

```
{
```

```
document.seats.newseats.value = "";
```

```
}
```

```
//-->
```

```
</SCRIPT>
```

```
<BODY BACKGROUND="images/background.jpg" TEXT="#000000" LINK="#006666"
```

```
VLINK="#006666">
```

```
<REM --- Begin database query to retrieve the last id number from table "orderdetail" for the  
purpose of creating a new instance of the stage image whenever a new order has occurred.
```

```
This will prevent the browser from displaying an old floor image from its cache as a different  
image name is called every time the file is run. --- >
```

```
<database DBNAME=":datasource"
```

```
database="SELECT max(id)
```

```
FROM orderdetail">
```

```
<databaseFETCH>
```

```
<iEQ NAME="imagenum" VALUE=:1>
```

```
<databaseFETCH>
```

```
</database>
```

```
<iEQ NAME="imagetype" VALUE=".jpg">
```

```
<CENTER>
```

```
<TABLE BGCOLOR='#000000' BORDER=0 CELLPADDING=5 CELLSPACING=0  
WIDTH=500>
```

```
<TR><TD><CENTER>
```

```
<FONT FACE='Verdana,Arial' SIZE=+1 COLOR='#FFFFFF'><B>
```

```
Concert Reservation System
```


</database>

</MAP>

<CENTER>

Click on the seat you wish to reserve.

<TABLE BORDER=1 CELLPADDING=0 CELLSPACING=0>

<TR><TD>

<REM --- Converts the dynamically generated image, "stage", into a web friendly image
type - "jpeg". --- >

<iIMAGEWRITE NAME="stage" FILENAME="images/ch_stage-:id-:imagenum:imagetype"
TYPE="jpeg" QUALITY="30">

<REM --- Deletes the temporary image "stage" as it is no longer needed. --- >

<iIMAGEDESTROY NAME="stage">

<IMG SRC="images/ch_stage-:id-:imagenum:imagetype" BORDER=0 USEMAP="#stage"
HEIGHT=315 WIDTH=584>

</CENTER>

</TD></TR></TABLE>

An "X" denotes a seat that has already been taken.

<FORM NAME="seats" ACTION="process.ihtml" METHOD="post">

<CENTER>

<TABLE BGCOLOR='#000000' BORDER=0 CELLPADDING=0 CELLSPACING=0>

<TR><TD>

<TABLE BGCOLOR='#FFFFFF' BORDER=0 CELLPADDING=5 CELLSPACING=1>

<TR><TD><CENTER>

Your mouse is over seat#: <INPUT TYPE="text" NAME="seatnum" SIZE=5>

0929557-04299
652240-455220

which then passes to a template:

```
<Markup language>

<REM --- Imports the file "datasource.inc" which creates the variable "datasource" which is
used to tell Markup language which ODBC datasource to connect to.

<iINCLUDE NAME="database\datasource.inc">

<REM --- In case a database or other type of error occurs, this will display the error
message. - >

<ERROR>

<FONT FACE="Verdana,Arial" SIZE="+1"><B>An Error Has Occurred</B></FONT><P>

<FONT FACE="Verdana,Arial" SIZE="-1"><B>Error Message =

:i_errortext</B></FONT><P>

<FONT FACE="Verdana,Arial" SIZE="-1"><B>database Error =

:i_databaseerrortext</B></FONT><P>

<FONT FACE="Verdana,Arial" SIZE="-1"><B>database Error =

:i_databaseerrorstmt</B></FONT><P>

</ERROR>
```

IX

```

<REM --- Copy a preformatted file, "empty.ihtml" into a new file, --- >

<REM --- "reserve2.ihtml". --- >

<iCOPYFILE SRC="empty.ihtml" DST="reserve2.ihtml">

<REM --- Appends the information passed from "reseve1.ihtml" to "reserve2.ihtml" for
process. Other html information is also passed. --- >

<iFILE NAME="reserve2.ihtml" DATA=":newseats" OP="append">

<iFILE NAME="reserve2.ihtml" DATA="<INPUT TYPE='hidden' NAME='total'
VALUE=:total>" OP="append">

<iFILE NAME="reserve2.ihtml" DATA="</FORM>" OP="append">

<iFILE NAME="reserve2.ihtml" DATA="</CENTER>" OP="append">

<iFILE NAME="reserve2.ihtml" DATA="<P>" OP="append">

<iFILE NAME="reserve2.ihtml" DATA="</BODY>" OP="append">

<iFILE NAME="reserve2.ihtml" DATA="</markup language>" OP="append">

<REM --- Once the information is appended into "reserve2.ihtml", it will be automatically
push the page "reserve2.ihtml" to the browser. --- >

<iREDIR URL="reserve2.ihtml">

```

which then combines information and passes to:

```

<Markup language>

<REM --- Imports the file "datasource.inc" which creates the variable "datasource" which is
used to tell Markup language which ODBC datasource to connect to. --- >

<iINCLUDE NAME="database\datasource.inc">

<REM --- In case a database or other type of error occurs, this will display the error
message. - >

<ERROR>

<FONT FACE="Verdana,Arial" SIZE="+1"><B>An Error Has Occurred</B></FONT><P>

<FONT FACE="Verdana,Arial" SIZE="-1"><B>Error Message =

:i_errortext</B></FONT><P>

<FONT FACE="Verdana,Arial" SIZE="-1"><B>database Error =

:i_databaseerrortext</B></FONT><P>

```

0929577.042299

```

<FONT FACE="Verdana,Arial" SIZE="-1"><B>database Error =
:i_databaseerrorstmt</B></FONT><P>

</ERROR>

<REM --- Copy a preformatted file, "empty.ihtml" into a new file, "reserve2.ihtml". --- >

<iCOPYFILE SRC="empty.ihtml" DST="reserve2.ihtml">

<REM --- Appends the information passed from "reseve1.ihtml" to "reserve2.ihtml" for
process. Other html information is also passed. --- >

<iFILE NAME="reserve2.ihtml" DATA=":newseats" OP="append">

<iFILE NAME="reserve2.ihtml" DATA="<INPUT TYPE='hidden' NAME='total'
VALUE=:total>" OP="append">

<iFILE NAME="reserve2.ihtml" DATA="</FORM>" OP="append">

<iFILE NAME="reserve2.ihtml" DATA="</CENTER>" OP="append">

<iFILE NAME="reserve2.ihtml" DATA="<P>" OP="append">

<iFILE NAME="reserve2.ihtml" DATA="</BODY>" OP="append">

<iFILE NAME="reserve2.ihtml" DATA="</markup language>" OP="append">

<REM --- Once the information is appended into "reserve2.ihtml", it will be automatically
push the page "reserve2.ihtml" to the browser.

<iREDIR URL="reserve2.ihtml">

then (takes all information from index & reserve one and combines it to with the information
in empty) then passes to:

<!Markup language>

<REM --- Imports the file "datasource.inc" which creates the variable "datasource" which is
used to tell Markup language which ODBC datasource to connect to. --- >

<iINCLUDE NAME="database\datasource.inc">

<REM -- In case a database or other type of error occurs, this will display the error message.
-- >

<ERROR>

<FONT FACE="Verdana,Arial" SIZE="+1"><B>An Error Has Occurred</B></FONT><P>

<FONT FACE="Verdana,Arial" SIZE="-1"><B>Error Message =
:i_errortext</B></FONT><P>

```

```

<FONT FACE="Verdana,Arial" SIZE="-1"><B>database Error =
:i_databaseerrortext</B></FONT><P>

<FONT FACE="Verdana,Arial" SIZE="-1"><B>database Error =
:i_databaseerrorstmt</B></FONT><P>

</ERROR>

<REM --- Begin normal markup language here          --- >

<markup language>

<HEAD>

<TITLE>Ticketing & Reservation System - Customer Information</TITLE>

</HEAD>

<BODY BACKGROUND="images/background.jpg" TEXT="#000000" LINK="#006666"
VLINK="#006666">

<REM ----- Get Customer Info ----- >

<CENTER>

<TABLE BGCOLOR='#000000' BORDER=0 CELLPADDING=5 CELLSPACING=0
WIDTH=500>

<TR><TD><CENTER>

<FONT FACE='Verdana,Arial' SIZE=+1 COLOR='#FFFFFF'><B>

Ticketing & Reservation System

</B></FONT>

</CENTER>

</TD></TR>

</TABLE><p>

<FORM ACTION=reserve3.ihtml METHOD=POST>

<TABLE BGCOLOR='#000000' BORDER=0 CELLPADDING=0 CELLSPACING=0>

<TR><TD>

<TABLE BGCOLOR='#FFFFFF' BORDER=0 CELLPADDING=5 CELLSPACING=1>

    <TR>

        <TD COLSPAN=2><CENTER><FONT FACE='Verdana,Arial' SIZE=-
1><B>CUSTOMER INFORMATION</CENTER></TD>

```

</TR><TR>

<TD>Name as appear on
CC</TD>

<TD><INPUT TYPE="text"
NAME="name" MAXLENGTH=50 SIZE=40></TD>

</TR><TR>

<TD>Phone</TD>

<TD><INPUT TYPE="text"
NAME="phone" MAXLENGTH=50 SIZE=12></TD>

</TR><TR>

<TD>Email</TD>

<TD><INPUT TYPE="text"
NAME="email" MAXLENGTH=50 SIZE=40></TD>

</TR><TR>

<TD>CC Number</TD>

<TD><INPUT TYPE="text"
NAME="ccnum" MAXLENGTH=50 SIZE=40></TD>

</TR><TR>

<TD>Expiration
(MM/YY)</TD>

<TD>Month <INPUT TYPE="text"
NAME="ccmexp" MAXLENGTH=50 SIZE=2> / Year <INPUT TYPE="text" NAME="ccyexp"
MAXLENGTH=50 SIZE=2> ... example: 12/99</TD>

</TR><TR>

<TD COLSPAN=2>

<CENTER>

<INPUT TYPE="submit" VALUE="Reserve Seats">

<INPUT TYPE="reset" VALUE="Clear Choices">

</CENTER>

</TD></TR>

</TABLE>

</TD></TR></TABLE>

<iEQ NAME="total" VALUE=0>

<iEQ NAME="date" VALUE='<iDATE>'

<REM --- Begin database command to insert a new customer profile into the database. This step is primarily for the purpose of obtaining a new customer id to associate this transaction.

The customer's ip and captured and inserted into a new record in the "customers" table.

The marker, "new" is flagged "true" for the attrieval of the new id. Once the new customer id is captured, the marker "new" is turned off. --- >

<Markup language DBNAME=:datasource

database="INSERT INTO customers (ip, new)

VALUES (:i_ip,1)">

<database DBNAME=:datasource

database="SELECT id

FROM customers

WHERE new=1">

<databaseFETCH>

<iEQ NAME="custid" VALUE=:1>

</database>

<Markup language DBNAME=:datasource

database="UPDATE customers

SET new=0

WHERE id=:custid">

<REM --- Begin database command to insert a new reservation into the database. This step is primarily for the purpose of creating a new reservation record, flagged with the newly obtained customer id, so that the transaction information may be processed in

"resere3.ihtml".

--- >

09295677442991662240" 44556260

<Markup language DBNAME=:datasource

database="INSERT INTO orders (orderdate, approvalcode, receiptnum, totalcharge, custid)

VALUES (:date, '0000', '0000', :total, :custid)"

FAILURE="The order could not be processed at this time due to technical difficulties.">

<REM --- Begin database command to obtain the reservation id that was just created. This information, coupled with the customer id, will be used to identify this particular transaction in the database and be updated in "resere3.ihtml" --- >

<database DBNAME=:datasource

database="SELECT max(id)

FROM orders">

<databaseFETCH>

<iEQ NAME="oid" VALUE=:1>

</database>

<INPUT TYPE="hidden" NAME="reserve" VALUE="receipt">

<INPUT TYPE="hidden" NAME=custid VALUE=:custid>

<INPUT TYPE="hidden" NAME=phone VALUE=:phone>

<INPUT TYPE="hidden" NAME=email VALUE=:email>

<INPUT TYPE="hidden" NAME=oid VALUE=:oid>

<Markup language DBNAME=:datasource database='INSERT INTO basket (custid, pid, qty)

VALUES (:custid, 6431, 1)'><database DBNAME=:datasource database='SELECT cost

FROM products WHERE id=6431'><databaseFETCH><iEQ NAME='ticketprice'

VALUE=:1></database><iEQ NAME='total' VALUE=<iEVAL EXPR=':ticketprice + :total'

PREC='2'>><Markup language DBNAME=:datasource database='INSERT INTO orderdetail

(pid, oid, qty, sell) VALUES (6431, :oid, 1, :ticketprice)'><Markup language

DBNAME=:datasource database='INSERT INTO basket (custid, pid, qty) VALUES (:custid,

6428, 1)'><database DBNAME=:datasource database='SELECT cost FROM products

WHERE id=6428'><databaseFETCH><iEQ NAME='ticketprice'

VALUE=:1></database><iEQ NAME='total' VALUE=<iEVAL EXPR=':ticketprice + :total'

PREC='2'>><Markup language DBNAME=:datasource database='INSERT INTO orderdetail

0929557.04299
162240" 4456260

```
(pid, oid, qty, sell) VALUES (6428, :oid, 1, :ticketprice)'><Markup language
DBNAME=:datasource database='INSERT INTO basket (custid, pid, qty) VALUES (:custid,
6429, 1)'><database DBNAME=:datasource database='SELECT cost FROM products
WHERE id=6429'><databaseFETCH><iEQ NAME='ticketprice'
VALUE=:1></database><iEQ NAME='total' VALUE=<iEVAL EXPR=':ticketprice + :total'
PREC='2'>><Markup language DBNAME=:datasource database='INSERT INTO orderdetail
(pid, oid, qty, sell) VALUES (6429, :oid, 1, :ticketprice)'><Markup language
DBNAME=:datasource database='INSERT INTO basket (custid, pid, qty) VALUES (:custid,
6430, 1)'><database DBNAME=:datasource database='SELECT cost FROM products
WHERE id=6430'><databaseFETCH><iEQ NAME='ticketprice'
VALUE=:1></database><iEQ NAME='total' VALUE=<iEVAL EXPR=':ticketprice + :total'
PREC='2'>><Markup language DBNAME=:datasource database='INSERT INTO orderdetail
(pid, oid, qty, sell) VALUES (6430, :oid, 1, :ticketprice)'><INPUT TYPE='hidden'
NAME='total' VALUE=:total></FORM></CENTER><P></BODY></markup language>
```

takes in credit card information and passes to:

```
<!Markup language>
<REM --- Imports the file "datasource.inc" which creates the variable "datasource" which is
used to tell Markup language which ODBC datasource to connect to.
<iINCLUDE NAME="database\datasource.inc">
<REM -- In case a database or other type of error occurs, this will display the error message.
-- >
<ERROR>
<FONT FACE="Verdana,Arial" SIZE="+1"><B>An Error Has Occurred</B></FONT><P>
<FONT FACE="Verdana,Arial" SIZE="-1"><B>Error Message =
:i_errortext</B></FONT><P>
<FONT FACE="Verdana,Arial" SIZE="-1"><B>database Error =
:i_databaseerrortext</B></FONT><P>
<FONT FACE="Verdana,Arial" SIZE="-1"><B>database Error =
:i_databaseerrorstmt</B></FONT><P>
</ERROR>
```

```

<REM --- Begin normal markup language here      --- >

<markup language>

<HEAD>

<TITLE>Ticketing & Reservation System - Confirmation</TITLE>

</HEAD>

<BODY BACKGROUND="images/background.jpg" TEXT="#000000" LINK="#006666"
VLINK="#006666">

<REM --- Checks to see if the instance "reserve" with a value of      --- >

<REM --- "receipt" is passed to this page.  If so, the codes within      --- >

<REM --- the iCASE and /iCASE tags are executed.  This is primarily      --- >

<REM --- for security purposes as the instanced "reserved" is only      --- >

<REM --- called in the step immediately before.  If a visitor      --- >

<REM --- accidentally stumbled upon this file, nothing will be run      --- >

<REM --- unless all previous steps are completed.      --- >

<iCASE ALIAS="reserve" VALUE="receipt">

<CENTER>

<TABLE BGCOLOR='#000000' BORDER=0 CELLPADDING=5 CELLSPACING=0
WIDTH=500>

<TR><TD>

<CENTER>

<FONT FACE='Verdana,Arial' SIZE=+1 COLOR='#FFFFFF'><B>

Concert Reservation System

</B></FONT>

</CENTER>

</TD></TR>

</TABLE>

</CENTER><p>

<REM --- Two steps are combined here:      --- >

<REM --- 1. The reservation information captured in      --- >

<REM --- "reserve2.ih.html" is passed to the iPAY tag which      --- >

```

```

<REM --- processes the information and passes it to CyberCash --- >
<REM --- for verification. If successful, the tag returns --- >
<REM --- "success", otherwise it returns a variation of "fail" --- >
<REM --- 2. iIF checks to see if the verification is a success or --- >
<REM --- failure. If successful, it will process the codes --- >
<REM --- immediately after it, which includes updating the --- >
<REM --- database with a successful reservation. If anything --- >
<REM --- other than "success" is returned, iIF will skip to --- >
<REM --- the iELSE tag and execute all codes thereafter. --- >
<iIF COND=<iPAY SERVER="C3"

```

```

    amount=:total
    id=:oid
    ccnum=":ccnum"
    ccmexp=":ccmexp"
    ccyexp=":ccyexp"
    name=":name"
    capture="false"
    HOST="http://cr.cybercash.com/cgi-bin"
    PORT=80
    SECRET="vendorid-26"
    CRYPTOKEY="j1y1o1ohNU1ciTdPF1hsvHFjlpnCpR">>

```

```
<CENTER>
```

```
<TABLE BGCOLOR='#000000' BORDER=0 CELLPADDING=0 CELLSPACING=0>
```

```
<TR><TD>
```

```
<TABLE BGCOLOR='#FFFFFF' BORDER=0 CELLPADDING=5 CELLSPACING=1
WIDTH=500>
```

```
<TR><TD>
```

```
<FONT FACE="Verdana,Arial" SIZE="-1">
```

```
<B>The credit card has been approved and the reservation has been processed.<P>
```

```
The following are the Authorization Code and Receipt Number:</B><p>
```

09295577.042299

XVIII

```

<b>Authorization Code:</b> :i_pay_authnumber<BR>
<b>Receipt Number:</b> :i_pay_transactionnumber<P>
<b>Customer Name:</b> :name<BR>
<b>Total Amount:</b> $:total<BR>
<b>Credit Card Number:</b> :ccnum<BR>
<b>Month of Expiration:</b> :ccmexp<BR>
<b>Year of Expiration:</b> :ccyexp<BR>
<REM --- Begin database query to update the "customers" table with customer information
captured in "reserve2.ihtml".      --- >

<Markup language DBNAME=:datasource

        database="UPDATE customers

        SET contact=':name', phone=':phone', email=':email'

        WHERE id=:custid">

<REM --- Begin database query to update the "orders" table is updated with the approval
code returned by CyberCash, as well as the transaction information (total charge, credit card
number, etc).                      --- >

<Markup language DBNAME=:datasource

        database="UPDATE orders

        SET approvalcode=':i_pay_authnumber',

receiptnum=':i_pay_transactionnumber', totalcharge=:total,cc=':ccnum', ccm=':ccmexp',

ccy=':ccyexp'

        WHERE id=:oid"

        FAILURE="The information was not saved correctly.<br>">

<REM --- Begin database query to turn off the availability of the seats that have been
reserved by setting the "active" attribute of the seats to "0".      --- >

<database ALIAS="markoff" dbname=":datasource" database="SELECT pid FROM
orderdetail WHERE oid=:oid">

        <databaseFETCH ALIAS="markoff">

        <iWHILE NOTALIAS=i_databaseempty>

                <Markup language dbname=":datasource"

```

0929557.04399

</database ALIAS="markoff">

Category	Item	Value
Category 1	Item 1	10
Category 1	Item 2	20
Category 2	Item 3	30
Category 2	Item 4	40
Category 3	Item 5	50
Category 3	Item 6	60
Category 4	Item 7	70
Category 4	Item 8	80
Category 5	Item 9	90
Category 5	Item 10	100

</TD></TR>

<CENTER>

<TR><TD>

WIDTH=500>

Information was invalid or the Cyber Cash server is currently not available.

</TD></TR>

</CENTER>

```
<FORM ACTION="index.html" METHOD="post">
```

XX

<CENTER>

<TABLE BGCOLOR='#000000' BORDER=0 CELLPADDING=0 CELLSPACING=0>

<TR><TD>

<TABLE BGCOLOR='#FFFFFF' BORDER=0 CELLPADDING=5 CELLSPACING=1

WIDTH=500>

<TR><TD>

<CENTER>

<INPUT TYPE="submit" VALUE="Return to Concert Selection">

</CENTER>

</TD></TR>

</TABLE>

</TD></TR>

</TABLE>

</CENTER>

</FORM>

<FORM ACTION="http://domainname/filename" METHOD="post">

<CENTER>

<TABLE BGCOLOR='#000000' BORDER=0 CELLPADDING=0 CELLSPACING=0>

<TR><TD>

<TABLE BGCOLOR='#FFFFFF' BORDER=0 CELLPADDING=5 CELLSPACING=1

WIDTH=500>

<TR><TD>

<CENTER>

<INPUT TYPE="submit" VALUE="Return to On-Line Ticketing & Reservation Front Desk">

</CENTER>

</TD></TR></TABLE></TD></TR></TABLE></CENTER>

</FORM>

092957.04299

</iCASE ALIAS="reserve">

</BODY>

</markup language>

which verifies and confirms payment information

End Figure 5

092957.042299
662240 1556260